





# Bostik

204802

M A T E R I A L   S A F E T Y   D A T A   S H E E T  
\*\*\*\*\*

PAGE 3

-----  
-                   SECTION V                   HEALTH HAZARD DATA (CONT.)                   -  
-----

air. If not breathing give artificial respiration, preferably mouth to mouth. If breathing is difficult give oxygen.  
Call a physician.

CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Call a physician.

IN CASE OF FIRE USE EXTINGUISHING AGENTS RECOMMENDED.

SYMPTOMS OF OVEREXPOSURE Irritation, Dizziness, Giddiness, Lightheadedness, Drunkenness, Incoherence, Breathing Difficulties.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Asthma, Respiratory Disease.

ENTRY ROUTE Contact, inhalation.

CHRONIC EFFECTS Long term overexposure to the hazardous materials in this product have been associated with Dermatitis, Dry, Brittle Skin.

TARGET ORGANS Central Nervous System, Skin, Lung.

NONE OF THE INGREDIENTS IN THIS PRODUCT EXCEEDING A CONCENTRATION LIMIT OF 0.1% ARE ON THE IARC, NTP, OR OSHA LISTS OF CARCINOGENIC HAZARDS

-----  
-                   SECTION VI                   REACTIVITY DATA                   -  
-----

STABILITY Stable

MATERIALS TO AVOID Strong Oxidizers, Alkalis, Strong Acids, Amines.

HAZARDOUS DECOMPOSITION PRODUCTS

Unknown due to the complex nature of this material. Fumes from complete or incomplete combustion of this material may include carbon dioxide, carbon monoxide, water vapor, oxides of nitrogen or a wide variety of innocuous or toxic fumes. Hydrofluoric Acid may also be produced.

HAZARDOUS POLYMERIZATION Will not occur.



204802

M A T E R I A L   S A F E T Y   D A T A   S H E E T  
\*\*\*\*\*

PAGE 4

-----  
-           SECTION VII                   SPILL OR LEAK PROCEDURES           -  
-----

STEPS TO BE TAKEN WHEN MATERIAL IS SPILLED OR RELEASED

WARNING, EXTREMELY FLAMMABLE! ELIMINATE ALL SOURCES OF IGNITION.

Soak up liquid with an absorbent material such as sand, earth, sweeping compound or some other absorbent material. Package absorbent material or solid product in steel drums which are in good condition. Thoroughly clean area where spill occurred.

WASTE DISPOSAL METHOD   Dispose of in accordance with federal, state, and local rules. Be aware that state and local requirements may differ widely depending on location and may in many cases be different from federal rules. When intending to dispose of this material, the user is advised that this product would be classified as a Hazardous Waste under U.S. federal Regulations in effect at the time this MSDS was created.

D001 Characteristic Ignitable Waste

-----  
-           SECTION VIII                   SPECIAL PROTECTION INFORMATION           -  
-----

VENTILATION            Local exhaust is preferred to keep vapors/particulates below the TLV value. Mechanical areawide ventilation is acceptable.  
PROTECTIVE GLOVES    Neoprene rubber, Nitrile, Impervious plastic.  
EYE PROTECTION        Safety glasses are recommended.  
OTHER PROTECTION     Safety shower and eye bath.

-----  
-           SECTION IX                    SPECIAL PRECAUTIONS                   -  
-----

PRECAUTIONS FOR HANDLING AND STORING

Store in a cool location (60-80 degrees F) away from sunlight and any source of heat, sparks or flame. Keep container tightly closed when not being used.

OTHER PRECAUTIONS

Use with adequate ventilation, avoid prolonged or repeated breathing of vapors. Avoid skin contact. Use in an area free from flame and sparks.

BOSTIK, INC., BOSTON STREET, MIDDLETON, MA 01949 USA  
TEL. 508-777-0100 FAX 508-750-7212



