

Material Safety Data Sheet

(Approved by US Department of Labor "Essentially Similar to form OSHA-20)

Emergency Telephone: 502 267 7717

Flexible Materials Inc.

11209 Electron Drive

Louisville, KY 40299

Date: June 1, 1992

Section 1 -- Identification

| | |
|------------------------------------|----------------------|
| Product Name | Chemical Name |
| Pre-applied Hot Melt Adhesive | E.V.A. Resin |
| Tradename | DOT Hazard Class |
| Pre-glued Woodtrim, Polyester, PVC | None, not restricted |

Section 2 -- Important Components

| | |
|--|------------------------------------|
| Description | Permissible Exposure Concentration |
| A mixture of etutlene vinyl acetate resins, rosins, and additives. | Not regulated |

Section 3 -- Physical Data

| | | | |
|----------------------|---------------|------------------|-----------|
| Boiling Point | N/A | Specific Gravity | N/A |
| Vapor Pressure | N/A | Percent Volatile | N/A |
| Vapor Density | N/A | Evaporation Rate | N/A |
| Solubility in Water | N/A | V. O. C. | .0 lb/gal |
| Appearance and Odor: | Slight if any | | |

Section 4 -- Fire and Explosion Data

| | |
|---|-------------|
| Flammability Classification | Flash Point |
| Not a falamable liquid. Solid Will support combustion | N/A |
| Extinguishing Media | |
| Water, Foam, CO2 | |
| Unusual Fire and Explosion Hazards | |
| None known | |
| Special Fire Fighting Procedures | |
| Firefighters should wear self-contained breathing apparatus to avoid inhalation of smoke or vapors. | |

This information is furnished without warranty representation, inducement of license of any kind, except that it is accurate to the best of Flexible Materials Inc.'s knowledge, or obtained from sources believed by Flexible Materials Inc. to be accurate, and Flexible Materials Inc. does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests.
Before using any product, read its label.

A:HOTMELT:WK1

Section 5 — Health Hazard Data

Effects of overexposure

Eyes, skin, nose & throat irritant upon overexposure. Avoid continued exposure if indicated.

Emergency and First Aid Procedures

Wear gloves, goggles and approved masks. Flush skin and eyes with clean water and consult a doctor.

Section 6 — Reactivity Data

Stability

Stable, burning may produce mixed aldehydes and hydrocarbons.

Hazardous Decomposition Products

Smoke and fire if ignited. Acrid and choking fumes may also be liberated. Wear approved self contained breathing apparatus to fight fire.

Hazardous Polymerization

Will not occur

Conditions to avoid

Open flame and ignition

Section 7 — Spill or Leak Procedures

Steps to be taken in case material is released or spilled

Sweep up and place in closed container.
Wear a dust mask if dust is created.

Waste Disposal Method

Incinerate in approved incinerator or dispose of in a chemical dump in accordance with local state and federal reg

Section 8 — Special Protection Information

Respiration Protection

Refer to OSHA 29 CFR 1910-134 "Respiratory Protection"
Avoid breathing fumes.

Ventilation

Ensure adequate ventilation

Protective Gloves

Leather gloves recommended

Eye Protection

Goggles recommended

Other Protective Equipment

Masks recommended for organic vapors.

Section 9 — Special Precautions

Precautions to be taken in handling and storing

Store in cool dry location

Other Precautions

Consult application instructions or labels prior to using this material