

Material Safety Data Sheet

(Approved by US Department of Labor "Essentially Similar to form OSHA-20)

Emergency Telephone: 502 267 7717

Flexible Materials Inc.

11209 Electron Drive

Louisville, KY 40299

Date: August 31, 1996

Section 1 -- Identification

Product Name	Chemical Name
PRESSURE SENSITIVE ADHESIVE	N/A
Tradename	DOT Hazard Class
FLEXWOOD P.S.A.	N/A

Section 2 -- Important Components

Description	Permissible Exposure Concentration
Acrylic Polymer on a Polycoated Kraft Paper - Silicone Release	Not regulated - this product is an "Article" as defined by OSHA Standard 29 C.F.R. 1910.1200

Section 3 -- Physical Data

Boiling Point	N/A	Specific Gravity	(A. 0.850 g./cc
Vapor Pressure	N/A	Percent Volatile	< 1.00 %
Vapor Density	N/A	Evaporation Rate	N/A
Solubility in Water	N/A		
Appearance and Odor: Slight Acrylate Odor When Un-rolled			

Section 4 -- Fire and Explosion Data

Flammability Classification	Flash Point
Will support combustion Rated -1	70.00 - 80.00 C
Extinguishing Media	
Water, Foam, CO2, Dry Chemical	
Unusual Fire and Explosion Hazards	
None known	
Special Fire Fighting Procedures	
Firefighters should wear self-contained breathing apparatus to avoid inhalation of smoke or vapors.	

This information is furnished without warranty representation, inducement of license of any kind, except that it is accurate to the best of Flexible Materials Inc.'s knowledge, or obtained from sources believed by Flexible Materials Inc. to be accurate, and Flexible Materials Inc. does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests. Before using any product, read its label.

A:MSDPSA.WK1

Section 5 — Health Hazard Data

Effects of overexposure

Eyes, skin, nose & throat irritant upon overexposure. Avoid continued exposure if indicated. Rated -0

Emergency and First Aid Procedures

Wear gloves, goggles and approved masks. Flush skin and eyes with clean water and consult a doctor.

Section 6 — Reactivity Data

Stability

Stable Rated -0

Hazardous Decomposition Products

Smoke and fire if ignited. Acrid and choking fumes may also be liberated. Wear approved self contained breathing apparatus to fight fire.

Hazardous Polymerization

Will not occur

Conditions to avoid

Open flame and ignition

Section 7 — Spill or Leak Procedures

Steps to be taken in case material is released or spilled

Will Not Spill

Waste Disposal Method

Dispose of in a landfill in accordance with local, state and federal regulations

Section 8 — Special Protection Information

Respiration Protection

Not required. Ventilate area if product is heated.

Ventilation

Ensure adequate ventilation

Protective Gloves

Avoid unnecessary skin contact

Eye Protection

Avoid eye contact

Other Protective Equipment

Section 9 — Special Precautions

Precautions to be taken in handling and storing

Store in cool dry location

Other Precautions

Consult application instructions or labels prior to using this material