

CLEARLY SUPERIOR

UV  
WOOD™



# At Columbia Forest Products, only the best will do.

So it's no surprise that we build our UV Wood panels to be the best.

You can see it all the way through. UV Wood is a beautiful, finished hardwood plywood panel featuring a clear, durable topcoat that manufacturers will love. Why? First of all, it increases productivity. With less surface to finish, workers are able to efficiently spend their time on other tasks. And since increasing productivity also increases profit, they'll love it even more.

They'll love its durability and versatility, as well. The epoxy acrylate finish is tough. It resists scratches, chips and the effects of solvent wipe down. Plus, UV Wood is available in satin, medium and high gloss, can be finished on one or two sides, and is available on any core, grade and species combination. It's perfect for kitchen cabinets, store fixtures, or anywhere a durable, clear finish is required. That's clearly a superior product.

They'll also love it because it's available. We have finishing plants on both sides of the country, so getting UV Wood is never a problem. Now your customers can get their shipments quickly and get their product out even faster. And that makes you look good. For more information, call 1-800-237-2428 (East) or 1-800-547-1791 (West), or visit us at [www.columbia-forestproducts.com](http://www.columbia-forestproducts.com).



Sturdi-Craft, Klamath Falls, Oregon

## Features & Benefits

- Beautiful, durable finish resists scratches and chips
- Finished surface reduces labor time, increasing productivity and efficiency
- Advanced sanding technology for a smoother, more beautiful appearance
- UV finished surface reduces VOC emissions
- Regional finishing facilities for consistent availability and prompt delivery
- Available in a variety of core thicknesses and hardwood face and back combinations for numerous design options

## Specifications

|                                   |            |                         |  |                    |              |  |  |      |
|-----------------------------------|------------|-------------------------|--|--------------------|--------------|--|--|------|
| <b>Finish Thickness Dry</b>       | .8-1.0 mil | <b>Durability</b>       | Excellent  | <b>Gloss Level</b> | Satin        | 30 - 40% reflection (Specify at time of order placement) | <b>Effects of Common Household Staining Agents</b> | None |
| <b>% Solids Applied</b>           | 100%       | <b>Machinability</b>    | Excellent  |                    |              |  | <b>Special Tooling Required</b>                    | None |
| <b>VOC Emissions</b>              | None       | <b>Wood Preparation</b> | Cross grain and long grain sanded to ensure maximum smoothness |                    | Medium gloss | 50 - 60% reflection (Standard)                           |  |      |
| <b>Effect of Water or Solvent</b> | None       |                         |  |                    | High gloss   | 80 - 90% reflection (Specify at time of order placement) |  |      |
| <b>Acetone Wipe Down</b>          | Yes        |                         |  |                    |              |  |  |      |
| <b>AWI/NKB/ANSI Standard</b>      | Exceeds    |                         |  |                    |              |  |  |      |

Proud sponsor of

